

Han GigaBit Cat8 (GND), male



Part number	09 14 008 3035
Specification	Han GigaBit Cat8 (GND), male
HARTING eCatalogue	https://b2b.harting.com/09140083035

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Inserts
Type of module	Han [®] Gigabit module
Description of the module	Insert
Features	Suitable for PoE++

Version

Termination method	Crimp termination
Gender	Male
Number of contacts	8
further contacts	+ shielding
	With additional shield connection to the hinged frame
Details	Please order crimp contacts separately.
	Please order adapter module separately.

Technical characteristics

Conductor cross-section	0.09 0.52 mm²
Rated current	5 A
Rated voltage	50 V
Rated voltage	50 V AC 60 V DC
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	30 V



Technical characteristics

Transmission characteristics	Cat. 7 _A Class F _A up to 1,000 MHz Cat. 8 Class II up to 2000 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s 25 Gbit/s 40 Gbit/s
Contact resistance, shielding	≤100 mΩ
Limiting temperature	-40 +85 °C
Mating cycles	≥500

Material properties

Polycarbonate (PC)
RAL 7032 (pebble grey)
Zinc die-cast, nickel-plated
V-0
compliant
compliant
е
Not contained
Not contained
Not contained
EN 45545-2 (2020-08)
R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
Approvals	DNV GL

Commercial data

Packaging size	1
Country of origin	Germany

Product data sheet 09 14 008 3035 Han GigaBit Cat8 (GND), male



Commercial data

European customs tariff number	85389099
GTIN	5713140187498
ETIM	EC000438
eCl@ss	27440218 Module for industrial connectors (data)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09140083035